

NEW

Alliance

Affordable quality · Proven reliability · Since 2006



Alliance FOUSI 34 Inverter Midwall Split

- Moneysaving Inverter economy: EER of 3.13; COP of 3.27
- Single-phase indoor and outdoor units
- Indoor noise level: 39dB(A)(Lo)
- Indoor airflow: 1450m³/h (Hi)
- Max. refrigerant piping length: 40 metres
- Backed nationwide by Fourways Airconditioning South Africa



www.allianceair.co.za

Alliance FOUSI 34 Inverter Midwall Split

With electricity prices ever on the up-and-up, Inverters are becoming the big new trend in airconditioning. Alliance's new FOUSI 34 Inverter midwall is not only very economical to run (EER of 3.13), but is also competitively priced. With an application area from 46 m² to 67m², it's suitable for large interiors, while its sleek design enhances any décor. And because it's backed by the nationwide might of Fourways Airconditioning, you can have total peace of mind regarding future parts and technical support.



| Indoor Model | | | FOUSI34 |
|-------------------------------------|------------------------------|-------------------|---------------------------------|
| Outdoor Model | | | FOUSI34X |
| Power supply | | Ph-V-Hz | 220-240V,1Ph,50Hz |
| Cooling | Capacity | Kw | 10,1 |
| | Input | W | 3230 |
| | Rated current | A | 14.5 |
| | EER | W/W | 3.13 |
| Heating | Capacity | Kw | 10,3 |
| | Input | W | 3150 |
| | Rated current | A | 13.8 |
| | COP | W/W | 3.27 |
| Max. input consumption | | W | 5175 |
| Max. current | | A | 22.5 |
| Compressor | Refrigerant oil/oil charge | ml | VG74 / 1000 |
| Indoor air flow (Hi/Mi/Lo) | | m ³ /h | 1450 / 1090 / 810 |
| Indoor noise level (Hi/Mi/Lo) | | dB(A) | 51 / 44 / 39 |
| Indoor unit | Dimension(W x D x H) | mm | 1259 x 282 x 362 |
| | Net/Gross weight | Kg | 19.0 / 26.5 |
| Outdoor Model | | | FOUSI34X |
| Outdoor noise level | | dB(A) | 64 |
| Outdoor unit | Dimension(W x D x H) | mm | 946 x 420 x 810 |
| | Net/Gross weight | Kg | 69 / 75 |
| Refrigerant type | | Kg | R410A / 3.50 |
| Design pressure | | MPa | 4.2 / 1.5 |
| Refrigerant piping | Liquid side/ Gas side | mm(inch) | 9.52mm (3/8in) / 15.9mm (5/8in) |
| | Max. refrigerant pipe length | m | 40 |
| | Max. difference in level | m | 20 |
| Thermostat type | | | Remote Control |
| Operation temperature | | °C | 17~30 |
| Room temperature | Indoor(cooling/ heating) | °C | 18~32 / 0~27 |
| | Outdoor(cooling/heating) | °C | -15~46 / -15~24 |
| Application area (Cooling Standard) | | m ² | 46~67 |

Alliance reserves the right to discontinue or change specifications at any time without notice and without incurring obligation. E&OE.

Alliance

Affordable quality · Proven reliability · Since 2006